



## AQUEOUS TECHNOLOGIES CORPORATION

9055 Rancho Park Court, Rancho Cucamonga, CA 91730

Phone: 909.944.7771 • Fax: 909.944.7775 • [www.aqueoustech.com](http://www.aqueoustech.com)

### Clean Matters

by Michael Konrad President Aqueous Technologies Corporation

In almost every context, clean is good and not clean is bad. In almost every industry, internal components are cleaned before installation. At times, the electronics assembly industry is an exception to the rule.

As I have mentioned in more than one past article, I have been involved in electronics assembly cleaning — more specifically defluxing — for more than 20 years. Perhaps that is why I look at the world in terms clean or not clean.

In almost every context, clean is good and not clean is bad. When an Olympic athlete's drug test comes back clean, that's good. One is relieved to receive a clean bill of health. A clean sweep by your favorite sports team is cause for celebration and who doesn't want to clean up in Las Vegas?

The most common dictionary definitions of clean include free from dirt, extraneous matter, irregularity, defects, etc. In almost every industry, internal components are cleaned before installation. When substances are left on a part — grease on a gear for example — the substance specifically adds value to the component. At times, the electronics assembly industry is an exception to this rule. In many segments of our industry, cleaning and maintaining a clean environment are considered vital to the successful production of a product. Anyone who has to don cleanroom garments knows the costs of contamination. There is a segment of our industry that seems to ignore the value of a clean product.

When electronic components are soldered to a PCB, flux is applied to prevent oxidation of the heated molten solder, improving a solder joint's integrity. Flux has a distinct and specific purpose. Once that purpose has been achieved, the remaining flux residue serves no other purpose. In fact, the remaining residue is a contaminant, still conductive and corrosive.

Virtually without exception, all manufacturers of electronics assemblies used in high-reliability applications remove flux after reflow. The military requires defluxing to specific cleanliness levels, and many other industries also require defluxing. Manufacturers of medical devices remove flux residues from their assemblies to improve product reliability. Commercial aircraft manufacturers clean all flight boards to eliminate residue-caused defects. Space, broadcasting, emergency response, and hundreds of other high-reliability industries all implement flux residue removal procedures within their assembly processes.

The turn of the 21st century introduced an interesting phenomenon into our industry. Defluxing, formally a practice of high-reliability manufacturers, began to trickle down to manufacturers of less-critical devices. For example, manufacturers of audio amplifiers determined that removing flux from circuit assemblies resulted in truer sounds, with less distortion. One major manufacturer informed me that their version of cleanliness testing was plugging in a guitar and listening to the amplified sound. They can hear the presence of flux residue on the board.

Unfortunately, flux residue does not often expose itself audibly. In most applications, remaining flux residues attack the assembly over time. The time required to generate a failure can be accelerated when heat and humidity are factors because both accelerate corrosion and dendritic growth.